

# towDOLLIES



## Standard Features

- We use Sure-Lube hubs which ease the repacking of wheel bearings by eliminating the need for disassembly, and are backed by a 2-year warranty.
- All of our dollies are equipped with new tires and wheels that are computer balanced to assure a smooth ride at all towing speeds.
- Our ramps and carrying pan tilt rearward for loading and feature a raised tread grip pattern that gives extra traction making the Tilt-Bed Loading safer and easier.
- Our fenders are molded of ¼" thick polyethylene which eliminates metal fatigue problems common with steel fenders, and they will not scratch or rust. They house oval waterproof clearance and tail lights that are rubber-mounted in a low profile design for longer bulb life and maximum clearance in tight turns.
- The carrying pan steers for your car by swiveling smoothly on polyethylene pads which are maintenance free.
- Both safety chains have a unique s-hook safety closure added to insure their secure attachment to the tow vehicle at all times.
- A factory molded plug-together wiring harness is used to eliminate the need for wire splices which often corrode and lead to wiring shorts. It is also poly loomed where exposed and carefully routed outside the fender well to prevent wires from being damaged by debris thrown up from the tire.
- We use an exclusive painting process which involves chemically cleansing and etching the bare metal before applying a primer and 2-coat acrylic enamel finish. This extra effort keeps our dollies looking better longer.
- 10,000 pound rated ratchets and adjustable straps securely fasten most 13" through 16" tires and wheels.
- Every Master Tow dolly is backed by a 1-year written warranty to show our commitment to quality.

## 3 models available to meet all your towing needs

**Model 77T**  
For towing small to  
mid-size cars  
(towed vehicle tread width 40" - 77")

**Model 80T**  
For towing small to  
full-size cars  
(towed vehicle tread width 40" - 80")

**Model 80THD (Heavy Duty)**  
For towing small to  
full-size cars, vans & trucks  
(towed vehicle tread width 40" - 80")

Visit us at [www.mastertow.com](http://www.mastertow.com)

MASTER TOW

# MASTER TOW

## Available Options



14" Radial Tire



Electric Brakes  
Break Away Kit



Electric & Surge  
Drum Brakes



Surge Stainless  
Disc Brakes

## Available Accessories



Spare Tire &  
Mount Kit



Towed Vehicle  
Secure Chains



Bolt On Winch Kit



Magnetic Light Kit

## Specifications

MODEL	77T	80T	80THD
Towed Vehicle Tread Width (min-max)	40" - 77"	40" - 80"	40" - 80"
Maximum Overall Width at Front Doors for Vehicle in Tow	75"	78"	78"
Overall Width	99"	102"	102"
Overall Length	121.5"	121.5"	121.5"
Height at Fender	26"	26"	26"
Ground Clearance	6"	6"	6"
Empty Weight	450 lbs.	483 lbs.	551 lbs.
Gross Vehicle Weight Rating	3,500 lbs.	3,500 lbs.	3,500 lbs.
Tire Size (Trailer Service)	ST 205/75 14" 6 Ply Rated	ST 205/75 14" 6 Ply Rated	ST 205/75 14" 6 Ply Rated
Coupler Size	2"	2"	2"
Coupler Class	SAE 2/3,500 lbs.	SAE 2/3,500 lbs.	SAE 3/5,000 lbs.
Axle Tube Thickness	3/16"	3/16"	1/4"
2" x 2" x 3/16" Tubular Steel Reinforced Carrying Pan	NO	NO	YES

### CONTACT:



## MASTER TOW

783 Slocomb Road  
Fayetteville, NC 28311  
(910) 630-2000 • 1-800-522-2190  
Fax (910) 630-2016  
Email: [mastertow@mastertow.com](mailto:mastertow@mastertow.com)  
Web: [www.mastertow.com](http://www.mastertow.com)